


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b> <b>B01L 3/02</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/13796</b> <b>(43) International Publication Date:</b> 16 March 2000 (16.03.00)
<b>(21) International Application Number:</b> PCT/US99/20692 <b>(22) International Filing Date:</b> 9 September 1999 (09.09.99)  <b>(30) Priority Data:</b> 09/150,502 9 September 1998 (09.09.98) US  <b>(71) Applicant:</b> INCYTE PHARMACEUTICALS, INC. [US/US]; 3174 Porter Drive, Palo Alto, CA 94304 (US).  <b>(72) Inventors:</b> SHALON, Tidhar, D.; Incyte Microarray, 6519 Dumbarton Circle, Fremont, CA 94555 (US). MAURINO, Joseph, R.; Incyte Microarray, 6519 Dumbarton Circle, Fremont, CA 94555 (US). TITSWORTH, Loren, D.; Incyte Microarray, 6519 Dumbarton Circle, Fremont, CA 94555 (US). BEVIRT, JoeBen; Incyte Pharmaceuticals, Inc., 3174 Porter Drive, Palo Alto, CA 94304 (US).  <b>(74) Agent:</b> OSMAN, Richard, Aron; Science & Technology Law Group, 75 Denise Drive, Hillsborough, CA 94010 (US).		<b>(81) Designated States:</b> AU, CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> CAPILLARY PRINTING SYSTEMS  <b>(57) Abstract</b> <p>The invention provides printing systems and methods for depositing small volumes of liquid on solid substrates. These systems and methods are useful with a wide variety of liquids and substrates and offer a wide variety of applications, including the deposition of arrays of analytes. In particular embodiments, the systems comprise a preservation device, a detachable ganged plurality of printing devices, and/or a wire bonding capillary.</p> 		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

*Capillary Printing Systems*

5

## INTRODUCTION

## 10 Field of the Invention

The invention is in the field of capillary printing systems and their fabrication.

## Background

15 The accurate dispensing and deposition on a substrate of small volumes of liquid has been effected with a variety of printing instruments including micropipettes and injectors (see, e.g. US Pat Nos. 4,815,325; 5,601,980; 5,747,102), ink-jet printers (see, e.g. US Pat No. 5,338,688), and fountain-pen type contact-deposition capillaries (see, e.g. WO95/35505 and US Pat No. 5,770,151). In addition, a number of multiport liquid transfer and delivery apparatuses are commercially available (e.g. MICROLAB® DNA Workstation by Hamilton  
20 Co., Reno NV; HYDRA Microdispenser by Robbins Scientific, Sunnyvale CA; Microarray Printing System by Genometrix, The Woodlands, TX). While some of these instruments have been used to print ordered analytical or probe arrays, they offer various relative advantages and disadvantages, including differing print resolution, speed, cross-contamination control, probe tolerances, etc. For example, the cartridges utilized in ink-jet  
25 printers dispense a controlled volume of liquid by use of a pressure wave created within the cartridge and which results from a sharp temperature increase to the ink that can damage or shear a molecularly fragile probe. Existing pipettors and contact deposition capillaries are better suited to printing fragile probes but require washings between different probe loadings and offer limited print resolution. The present invention provides improved printing systems  
30 particularly suited for printing high-density analytical arrays.

## SUMMARY OF THE INVENTION

The invention provides printing systems and methods for depositing small volumes of liquid on solid substrates. These systems and methods are useful with a wide variety of

liquids and substrates and offer a wide variety of applications, including the deposition of arrays of analytes, such as chemical and biochemical library arrays.

In one embodiment, the invention provides a printing system comprising a pod, a detachable printing device, a substrate, a positioner and a preservation device, wherein (a) the pod comprises a receptacle for reversibly attaching an attachment portion of the printing device; (b) the printing device comprises a reservoir containing a liquid comprising a predetermined agent and in fluid connection with the reservoir, a capillary comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent on the substrate; (c) the positioner moves the pod relative to the substrate; and (d) the preservation device is within, containing or in contact with the printing device and preserves the capability of the printing device to print the agent on the substrate over long-term storage. Generally, the preservation device provides a deterrent to evaporation of the liquid, such as a hermetic barrier, a refrigerator, a humidifier, a hygroscopic agent, etc. The system may also comprise a detachable ganged plurality of such printing devices.

In another embodiment, the invention provides a printing system comprising a pod, a detachable ganged plurality of printing devices, a substrate and a positioner, wherein (a) the pod comprises a receptacle for reversibly attaching an attachment portion of the printing devices; (b) each of the printing devices comprises a reservoir containing a unique agent and in fluid connection with the reservoir, a capillary comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent on the substrate; and (c) the positioner moves the pod relative to the substrate.

In another embodiment, the invention provides a printing system comprising a wire bonding capillary containing a predetermined agent and comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent. And in a more particular embodiment, the invention provides a printing system comprising a ganged plurality of wire bonding capillaries, each containing a different agent and comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent.

A wide variety of more particular embodiments of these systems are disclosed. For example, in one such embodiment, the capillary bore tapers toward the distal opening of the tip; in another, the system further comprises a motion resistor operatively joined to the capillary and providing an incomplete resistance to motion of the capillary along its longitudinal axis, wherein the resistance may be provided by springs, an elastomeric membrane, the weight of the capillary, etc.; in another, the printing device is of one-piece construction; in another, the system further comprises a register comprising a guide which contacts a registration portion of the printing device, distal to the attachment portion, and moves the tip relative to the substrate; etc.

The invention provides methods of making, using and storing the subject systems including methods for printing liquids comprising agents or analytes on substrates with the printing systems, particularly printing methods which comprise the step of decelerating the capillary to move the liquid through the bore, out the tip and onto the substrate, which method may be effected, for example, by tapping the tip onto the substrate.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows a schematic of a printing head providing a ganged plurality of printing devices. Fig. 2 shows a schematic of a spring block motion resistor, a printing head and a registration plate.

Fig. 3 shows a schematic of a single printing device in the context of spring block motion resistor, printing head and registration plate portions.

Fig. 4 shows a schematic of a plurality of printing devices in the context of block motion resistor, elastomeric sheet and printing head portions.

Fig. 5 shows a schematic of a single printing device in the context of foam plug spring block motion resistor and printing head portions.

Fig. 6 shows a schematic of an inserted capillary printing device and a machined in printing device in the context of plunger-bearing spring block motion resistor and printing head portions.

Fig. 7 shows a schematic of a printing head portion having compressable channel walls.

Fig. 8 shows a schematic of a single-piece construction low density multi-channel printing head.

Fig. 9 shows a schematic of a single-piece construction high density multi-channel printing head.

Fig. 10 shows schematic of a registration plate and a printing head comprising a floppy door preservation device.

- 5 Fig. 11 shows schematic of a registration plate housing a printing head comprising a floppy door preservation device with the door opened.

Fig. 12 shows a schematic of an open jewel box type preservation device housing a printing head.

- 10 Fig. 13 shows a schematic of a closed caddy box type preservation device housing a printing head.

Fig. 14 shows a schematic of an open caddy box type preservation device housing a printing head.

Fig. 15 shows a schematic of a spring block and an open pop-out box type preservation device housing a printing head.

- 15 Fig. 16 shows a schematic of a spring block depressing the printing head of an open pop-out box type preservation device.

Fig. 17 shows a schematic of a open, passive loading, vacuum evacuation printing tip system.

Fig. 18 shows a schematic of a valve-actuated, passive loading, vacuum evacuation, pressure purging printing tip system.

- 20 Fig. 19 shows a schematic of a valve-actuated, active loading, vacuum evacuation, pressure purging printing tip system.

Fig. 20 shows a schematic of a gravity or pressure loading, active purging printing tip system.

Fig. 21 shows a schematic of a high-throughput a printing system.

## 25 DETAILED DESCRIPTION OF PARTICULAR EMBODIMENTS OF THE INVENTION

The following descriptions of particular embodiments and examples are offered by way of illustration and not by way of limitation.

- In a first aspect, the invention provides a printing system comprising a pod, a detachable printing device, a substrate, a positioner and a preservation device, wherein (a) the  
30 pod comprises a receptacle for reversibly attaching an attachment portion of the printing device; (b) the printing device comprises a reservoir containing a liquid comprising a

predetermined agent and in fluid connection with the reservoir, a capillary comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent on the substrate; (c) the positioner moves the pod relative to the substrate; and (d) the preservation device is within, containing or in contact with the printing device and preserves the capability of the printing device to print the agent on the substrate over long-term storage. This system is specifically adapted for long-term storage of the printing device and is amenable to a wide variety of suitable pods, detachable printing devices, substrates, positioners, preservation devices, applications and more particular embodiments.

10           Suitable pods include any structural member that transfers the positioning of the positioner to the printing device through a receptacle for reversibly attaching an attachment portion of the printing device. For example, the pod may simply be the terminus of a mechanical arm of the positioner with an engaging recess for receiving the proximal (distal from the tip) end of a capillary printing device.

15           Suitable printing devices include any structural member which combines by fluid connection the requisite reservoir and capillary. For example, the printing device may simply be a capillary comprising a liquid-filled bore having a proximate reservoir portion and terminating at a distal portion comprising the printing tip. Alternatively, the reservoir may comprise a more voluminous non-capillary liquid filled chamber having a relatively larger internal diameter in fluid connection with a capillary comprising the printing tip. The reservoir portion of the printing device is adapted to contain and contains a liquid comprising a predetermined agent. The device may be made of any convenient and compatible material. For example, suitable capillary fabrication material ceramic, silicon, glasses, etc. The printing device is adapted or adaptable to contain, store and/or print a wide variety of liquids, including aqueous liquids, liquids comprising organic polar solvents such as alcohols, DMSO, acetonitrile, etc., nonpolar solvents such as benzene, chloroform, etc.

20           Suitable substrates include any material providing a suitable printing surface, and include sheets of glasses, ceramics, plastics, metals, silicon, acetate, cellulose (paper), etc. The substrate may provide a homogeneous surface or a surface offering differential surface chemistry, topography, etc. For example, the surface may offer predetermined printing sites adapted to receiving, binding, reacting, containing and/or retaining the printing fluid.

Suitable positioners include any device which provides the requisite positioning of the printing device to effect the desired printing sites on the substrate. Frequently, the positioner will provide a first positioning within the two-dimensional plane of the substrate surface and a second positioning perpendicular to the surface to effect contact printing on the surface.

- 5 The positioner is generally electromechanically operated by a computer controlled robot.

Generally, the preservation device of these systems provides a deterrent to evaporation of the liquid, such that printing can be interrupted for extended periods, such as days, preferably weeks, more preferably months and even years, and then resumed without reloading the printing device. In various embodiments, the systems suffer less than a 50%,  
10 preferably less than a 20%, more preferably less than a 5% degradation in printing capacity over the storage period, as measured by subsequent error or misprint frequency, fluid loss, etc., as compared with an otherwise comparable but uninterrupted system. A wide variety of suitable preservation devices may be used. In one example, the device comprises a hermetic barrier, such as a seal on the printing device or a container capable of receiving and housing  
15 the printing device, which provides a system that is relatively, preferably substantially, more preferably fully closed to the printing solvent liquid and vapor. These barrier or containment devices may also provide a solvent vapor distributor, such as an absorbent sponge wetted with the solvent of the printing fluid, within the closed system to further minimize evaporation. In another example, the device comprises a refrigerator to cool or preferably  
20 freeze the liquid in the capillary of the printing device. In yet another example, the device comprises a hygroscopic agent which is incorporated in the liquid in the capillary and reduces the volatility of the liquid. For example, where the solvent of the liquid is water, suitable agents include glycerol (e.g. 5 - 95%), salts, etc.

The printing system is adaptable to virtually any application of small volume, high  
25 resolution liquid printing. For example, a wide variety of chemical and biochemical libraries may be deposited, including libraries derived from random or directed synthetic schemes, natural products including genetic material, etc. A particular application is the deposition of high density arrays of biochemical reagents or analytes such as polypeptides and  
polynucleotides (polymers of amino acids and nucleotides, preferably at least 5, more  
30 preferably at least 15, more preferably at least 50, more preferably at least 150 monomer units in length), e.g. for effecting solid phase, preferably high throughput solid phase immuno



assays and hybridization assays.

More particular embodiments of this system include systems wherein the dimensions and composition of the printing device capillary bore interact with the fluid contained therein to maintain the fluid proximate to the distal opening of the capillary tip. For example, the  
5 capillary bore may be tapered, preferably conically tapered toward the distal opening of the tip.

In another more particular embodiment, the system further comprises a motion resistor operatively joined to the capillary and providing an incomplete resistance to motion of the capillary along its longitudinal axis, wherein the resistance may be provided by springs,  
10 an elastomeric membrane, the weight of the capillary, etc. Such a motion resistor is especially important to facilitate contact printing on relatively planar or flat surfaces, especially wherein the system comprises a plurality of printing devices which print in concert, wherein the resistor(s) permit simultaneous contact of the printing devices on the surface.

In another more particular embodiment, the printing device is of one-piece  
15 construction and/or comprises a wire bonding capillary, described below. The system may also comprise a detachable ganged plurality of printing devices.

In another more particular embodiment, the system further comprises a register comprising a guide which contacts a registration portion of the printing device, distal to the attachment portion, and moves the tip relative to the substrate; etc. A wide variety of  
20 registers are provided. A printing system comprising a register may further comprise first and second detachable printing capillaries comprising respective first and second probes, a pod comprising a receptacle for attaching one of the capillaries, a substrate upon which the capillaries deposit the probes, whereupon detachment of the first capillary and attachment of the second capillary after deposition of a first portion of a high density probe array by the first  
25 capillary on the substrate, the register is capable of positioning the second capillary at a sufficiently similar position relative to the substrate to permit deposition of a second portion of the array by the second capillary on the substrate. In this system, the capillaries and probes may be different or the same.

In a second aspect, the invention provides a printing system comprising a pod, a  
30 detachable ganged plurality of printing devices, a substrate and a positioner, wherein (a) the pod comprises a receptacle for reversibly attaching an attachment portion of the printing

devices; (b) each of the printing devices comprises a reservoir containing a unique agent and in fluid connection with the reservoir, a capillary comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent on the substrate; and (c) the positioner moves the pod relative to the

5 substrate. This system provides a wide variety of ways of ganging a plurality of printing devices. In one embodiment, the detachable ganged plurality comprises a block having receptacles or holes for and which laterally constrain each of the printing devices. Alternatively, a rigid or elastomeric band or clamp may be used to gang together the printing devices. In a preferred embodiment, these systems provide analyte-specific dedicated

10 printing devices.

In another embodiment of this aspect of the invention, a one-piece block fabricated from a single material element provides the detachable ganged plurality, increasing the precision, accuracy, repeatability, reliability, speed and permitted densities of spot deposition. Because it is made from a single material element this device is also easier and less expensive

15 to construct and maintain. A wide variety of standard microlithography, micromachining and/or microfabrication methods known to those in the art may be used to construct these devices including injection molding, embossing, etching methods such as deep reaction ionic etching (DRIE), electric discharge machining (EDM), deposition, computer numerical control (CNC) milling, etc. Accordingly, the devices may be manufactured from a wide variety of

20 materials depending on the selected manufacturing method, including plastics such as polycarbonate, polystyrene, polypropylene and PMMA; glasses and/or ceramics; semiconductor material such as silicon; and metals such as stainless steel. The devices may be constructed in a variety of formats in terms of nozzle density, head size, reservoir size, etc. Print precision and accuracy are provided by precision engineering specifications including:

25 nozzle surface (e.g. flatness) variation of less than 10, preferably less than 5, more preferably less than 2, more preferably less than 1  $\mu\text{m}$  across all the nozzle tips of a head and internozzle print volume and distance (center-to-center) variation of less than about 4, preferably less than about 2, more preferably less than 1, more preferably less than 0.5%. The nozzles may be spaced to provide direct loading from standard microtiter sample plates (e.g. 9 mm center-

30 to-center) or at higher densities wherein the reservoirs may be loaded with conventional microvolume liquid handling devices. In a particular embodiment, the nozzles are spaced to

correspond with the desired array density, avoiding the need for off-set printing.

In a third aspect, the invention provides a printing system comprising a wire bonding capillary containing a predetermined agent and comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and  
5 which prints the agent. Wire bonding capillaries are adapted from semiconductor manufacturing, where a wire bonding process is used to electrically connect metal bond pads formed on a semiconductor die to the leadfingers of a leadframe. In this process, a bond wire is threaded through a wire bonding capillary and the end of the wire protruding through the capillary tip is heated to a molten ball. The molten ball is then mechanically pressed by the  
10 bonding capillary against the heated bond pad to alloy the metallic elements of the wire and bond pad. The capillary is then moved to a bonding site on the designated leadfinger where the wire is pressed against the heated leadfinger to bond the wire, then tensioned and sheared. Wire bonding capillaries are well known in the semiconductor manufacturing art, are the subject of numerous publications and patents (see e.g. US Pat Nos. 3,894,671; 4,877,173;  
15 5,082,154; 5,558,270; 5,662,261) and are commercially available from a number of sources (e.g. Micro-Swiss of Kulicke & Soffa Industries, Inc., Willow Grove PA; Gaiser Tool Company, Ventura, CA; Small Precision Tools, Petaluma, CA, etc.)

In a more particular embodiment, the invention provides a printing system comprising a ganged plurality of wire bonding capillaries, each containing a different agent and  
20 comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent.

The invention provides methods of making, using and storing the subject systems including methods for printing liquids comprising agents or analytes on substrates with the printing systems, particularly printing methods which comprise the step of decelerating the  
25 capillary to move the liquid through the bore, out the tip and onto the substrate, which method may be effected, for example, by contact printing, e.g. tapping the tip onto the substrate. A wide variety of methods may be used for loading and/or unloading the printing devices, including passive capillary loading and unloading from the printing tip, vacuum-assisted unloading, active pressure purging, etc. Uninterrupted multi-head printing systems  
30 comprising 25 20x20 (400 nozzle) heads provide for offset printing 10,000 spot arrays on chip substrates at rates of at least 0.2 chips/sec., preferably 1 chip/ sec., more preferably at

least 5 chips/sec.

### EXAMPLES

Referring to Fig. 1, a plurality of printing devices **11** are shown housed in receptacles  
5 of a gang **12** comprising tabs **13** for attaching to a pod (not shown) of a printing system.

Referring to Fig. 2, a plurality of printing devices **11** are shown housed in receptacles  
of a gang print head **12** comprising tabs **13**. Above the print head **12** is a spring block **21**  
retaining a plurality of vertical actuators **22**. Below the print head **12** is a registration plate **23**  
comprising a plurality of registration apertures **24**.

10 Referring to Fig. 3, a printing device **11** is shown housed in a receptacle of a portion  
of a print head **12**. Above the portion of the print head **12** is a portion of a spring block **21** is  
shown retaining a vertical actuators **22** comprising a spring **31**, a spring shaft **32** comprising a  
vent **33**. Below the portion of the print head **12** is a portion of the registration plate **23**  
comprising a registration aperture **24**.

15 Referring to Fig. 4, a plurality of printing devices **11** are shown housed in receptacles  
of a portion of a print head **12**. Above the portion of the print head **12** is a spring and vent  
cavity block **41** and between the block **41** and the print head **12** is a punch vented latex spring  
sheet **42**.

Referring to Fig. 5, a printing device **11** is shown housed in a receptacle of a portion  
20 of a print head **12**. Above the portion of the print head **12** is a portion of a spring and vent  
cavity block **41** is shown retaining a quick-recovery open cell foam spring/vent combination  
**51**.

Referring to Fig. 6, an inserted capillary printing device **61** and a machined in printing  
device **62** are shown housed and formed, respectively, in receptacles of a portion of a print  
25 head **12**. Above the portion of the print head **12** is a spring block **63**. The spring block **63**  
contains spring-loaded plungers **64**, each comprising a spring **65**, a flange **66** and a shaft **67**,  
and positioned above the printing devices **61** and **62**.

Referring to Fig. 7, a plurality of machined in printing devices **62** are shown formed in  
receptacles of a portion of a print head **12**, wherein the capillary portion **71** of the devices **62**  
30 have compressible channel walls **72**.

Referring to Fig. 8, a single-piece construction low density (e.g. 64 tips/cm<sup>2</sup>) multi-

channel printing head **81** is shown in cross-section. The head **81** comprises injection molded reservoirs **82** in fluid connection with the capillary bores **83** of molded printing tips **84**.

Referring to Fig. 9, a single-piece construction high density (e.g. 400 tips/cm<sup>2</sup>) multi-channel printing head **91** is shown in cross-section. The head **91** comprises etched reservoirs **92** in fluid connection with the capillary bores **93** of etched printing tips **94**.

Referring to Fig. 10, a print head **12** with an operatively affixed closed floppy door preservation device **101** is shown in approach toward a registration plate **102** comprising a plurality of printing tip registration apertures **103**.

Referring to Fig. 11, a print head **12** with an operatively affixed open floppy door preservation device **101** is shown in contact with a registration plate **102** comprising a plurality of printing tip registration apertures **103**, wherein the open floppy door preservation device **101** is shown in a slide open orientation. In an alternative embodiment, the open floppy door preservation device **101** may be swung open.

Referring to Fig. 12, an open jewel box type preservation device **121** containing a saturated foam pad **122** is shown housing a print head **12**.

Referring to Fig. 13, a closed caddy box type preservation device **131** containing a saturated foam pad **122** is shown housing a print head **12**.

Referring to Fig. 14, an open caddy box type preservation device **131** containing a saturated foam pad **122** is shown housing a print head **12**.

Referring to Fig. 15, a pop-out box type preservation device **151** containing a saturated foam pad is **122** shown in open position housing a print head **12**. Above and approaching the print head **12** is shown a spring block **152**.

Referring to Fig. 16, a pop-out box type preservation device **151** containing a saturated foam pad is **122** shown in open position housing a print head **12**. Above and depressing the print head **12** is shown a spring block **152**.

Referring to Fig. 17, a printing device **11** comprising a vent hole **171** is shown housed in a linear bearing receptacle of a portion of a print head **12**. Below the portion of the print head **12** is a portion of a vacuum plate **172** comprising a vacuum aperture **173**.

Referring to Fig. 18, a printing device **11** is shown housed in a linear bearing receptacle of a portion of a print head **12**. Below the portion of the print head **12** is a portion of a vacuum plate **172** comprising a vacuum aperture **173**. In fluid connection with the

printing device **11** through tubing **181** is a valve three-way valve **182** alternatively connecting the device to atmospheric pressure, closure or pressurized nitrogen.

Referring to Fig. 19, a printing device **11** is shown housed in a linear bearing receptacle of a portion of a print head **12**. Below the portion of the print head **12** is a portion  
5 of a vacuum plate **172** comprising a vacuum aperture **173**. In fluid connection with the printing device **11** through tubing **181** are four two-way valves **191** parallel, alternatively connecting the device to closure or respectively, pressurized nitrogen, water, atmospheric pressure and vacuum.

Referring to Fig. 20, a printing device **11** is shown in fluid connection through tubing  
10 **181** with a sample reservoir **201**.

Referring to Fig. 21, a printing system **210** comprising a multihead printing assembly **211** rotatably attached to a multichip turntable **212**. The assembly **211** comprises a plurality of single-piece construction high density (400 tips/cm<sup>2</sup>) multi-channel detachable printing heads **91** joined to the assembly **211** through actuators **213** which provide positioning stages  
15 **214** and L-brackets **215** for attaching the print heads **91**. The turntable **212** provides chip receptacles **216** which position the chips **216** which provide a printing substrate. In operation, the actuators **213** simultaneously stamp their respective printing heads **91** on the corresponding chips **216**. Thereafter, the turntable **212** rotates one chip position and the necessary printing offset is effected by turntable **212** rotation, acutator **213** positioning, or both. As the printing  
20 on a given chip **216** is completed (e.g. a complete array is deposited), the chip **216** is removed from the turntable **212** and replaced with a new chip **216**, thereby providing uninterrupted printing.

All publications and patent applications cited in this specification are herein  
25 incorporated by reference as if each individual publication or patent application were specifically and individually indicated to be incorporated by reference. Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity of understanding, it will be readily apparent to those of ordinary skill in the art in light of the teachings of this invention that certain changes and modifications may  
30 be made thereto without departing from the spirit or scope of the appended claims.

## WHAT IS CLAIMED IS:

1. A printing system comprising a pod, a detachable printing device, a substrate, a positioner and a preservation device, wherein:
  - the pod comprises a receptacle for reversibly attaching an attachment portion of the printing device;
  - the printing device comprises a reservoir containing a liquid comprising a predetermined agent and in fluid connection with the reservoir, a capillary comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent on the substrate;
  - the positioner moves the pod relative to the substrate; and
  - the preservation device is within, containing or in contact with the printing device and preserves the capability of the printing device to print the agent on the substrate over long-term storage.
2. The printing system of claim 1, wherein the bore tapers toward the distal opening of the tip.
3. The printing system of claim 1 further comprising a motion resistor operatively joined to the capillary and providing an incomplete resistance to motion of the capillary along its longitudinal axis, wherein the resistor is selected from a plurality of springs, an elastomeric membrane and the weight of the capillary.
4. The printing system of claim 1 wherein the printing device is of one-piece construction.
5. The printing system of claim 1 further comprising a register comprising a guide which contacts a registration portion of the printing device, distal to the attachment portion, and moves the tip relative to the substrate.
6. The printing system of claim 1, wherein the preservation device comprises a deterrent to evaporation of the liquid, wherein the deterrent is selected from the group consisting of a

hermetic barrier, a refrigerator, a humidifier and a hygroscopic agent.

7. The printing system of claim 1 comprising a detachable ganged plurality of printing devices, each comprising a reservoir containing a unique agent and in fluid connection with the reservoir, a capillary having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent on the substrate, wherein the pod comprises a receptacle for reversibly attaching an attachment portion of the printing devices and the preservation device is within, containing or in contact with the printing devices and preserves the capability of the printing devices to print the agents on the substrate over long-term storage.

8. A method for printing an agent on a substrate comprising the step of printing an agent with the printing system of claim 1.

9. The method of claim 8, further comprising the step of decelerating the capillary to move the agent through the bore, out the tip and onto the substrate.

10. The method of claim 8 further comprising the step of decelerating the capillary to move the agent through the bore, out the tip and onto the substrate, wherein the decelerating step is effected by tapping the tip onto the substrate.

11. The method of claim 8 further comprising the step of decelerating the capillary to move the agent through the bore, out the tip and onto the substrate, wherein the decelerating step moves a predetermined amount of the liquid through the bore, out the tip and onto the substrate.

12. A printing system comprising a pod, a detachable ganged plurality of printing devices, a substrate and a positioner, wherein:

the pod comprises a receptacle for reversibly attaching an attachment portion of the printing devices;

each of the printing devices comprises a reservoir containing a liquid comprising a



unique agent and in fluid connection with the reservoir, a capillary comprising an axial bore having proximal and distal openings to ambient pressure and a printing tip comprising the distal opening and which prints the agent on the substrate; and  
the positioner moves the pod relative to the substrate.

5

13. The printing system of claim 12, wherein the bore tapers toward the distal opening of the tip.

14. A printing system of claim 12 further comprising a motion resistor operatively joined  
10 to the capillary and providing an incomplete resistance to motion of the capillary along its longitudinal axis, wherein the resistor is selected from a plurality of springs, an elastomeric membrane and the weight of the capillary.

15. The printing system of claim 12 wherein the printing devices are of one-piece  
15 construction.

16. The printing system of claim 12 further comprising a register comprising a guide  
which contacts a registration portion of each of the printing devices, distal to the attachment  
portion, and moves the tip relative to the substrate.

20

17. A method for printing an agent on a substrate comprising the step of printing an agent  
with the printing system of claim 12.

18. The method of claim 17, further comprising the step of decelerating the capillary to  
25 move the agent through the bore, out the tip and onto the substrate.

19. The method of claim 17 further comprising the step of decelerating the capillary to  
move the agent through the bore, out the tip and onto the substrate, wherein the decelerating  
step is effected by tapping the tip onto the substrate.

30

20. The method of claim 17 further comprising the step of decelerating the capillary to

move the agent through the bore, out the tip and onto the substrate, wherein the decelerating step moves a predetermined amount of the liquid through the bore, out the tip and onto the substrate.

- 5 21. A printing system comprising a printing device comprising a wire bonding capillary containing a liquid comprising a predetermined agent and comprising an axial bore having proximal and distal openings and a printing tip comprising the distal opening and which prints the agent.
- 10 22. The printing system of claim 21, wherein the bore tapers toward the distal opening of the tip.
23. The printing system of claim 21, further comprising a motion resistor operatively joined to the capillary and providing an incomplete resistance to motion of the capillary along  
15 a longitudinal axis, wherein the resistor is selected from a plurality of springs and an elastomeric membrane.
24. The printing system of claim 21 wherein the capillary is of one-piece construction.
- 20 25. The printing system of claim 21 further comprising a pod, a positioner, a substrate and a register, wherein,  
the pod comprises a receptacle for reversibly attaching an attachment portion of the capillary;  
the positioner moves the pod relative to the substrate; and  
25 the register comprises a guide which contacts a registration portion of the capillary, distal to the attachment portion, and moves the tip relative to the substrate.
26. The printing system of claim 21 wherein the proximal and distal openings are open to ambient pressure.
- 30 27. The printing system of claim 21 wherein the agent is a polynucleotide.

28. The printing system of claim 21 comprising a ganged plurality of wire bonding capillaries, each containing a liquid comprising a different agent and comprising an axial bore having proximal and distal openings and a printing tip comprising the distal opening and which prints the agent.

5

29. The printing system of claim 28 wherein the agent is a member of a chemical library.

30. A method for printing an agent on a substrate comprising the step of printing on a substrate an agent with the printing system of claim 21.

10

31. The method of claim 30, further comprising the step of decelerating the capillary to move the agent through the bore, out the tip and onto the substrate.

32. The method of claim 30 further comprising the step of decelerating the capillary to move the agent through the bore, out the tip and onto the substrate, wherein the decelerating step is effected by tapping the tip onto the substrate.



15

33. The method of claim 30 further comprising the step of decelerating the capillary to move the agent through the bore, out the tip and onto the substrate, wherein the decelerating step moves a predetermined amount of the liquid through the bore, out the tip and onto the substrate.


20


HEADS w /TAC TIPS

variation #1




variation #2






TIP VARIATION



WO 00/13796

3/8

PCT/US99/20692














Fig 91











7/8/98

CASE TV a

GRAVITY OR PRESSURE LOAD  
 ACTIVE PURGE





# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 99/20692

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B01L3/02

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B01L B41J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 95 35505 A (UNIV LELAND STANFORD JUNIOR) 28 December 1995 (1995-12-28) cited in the application the whole document	1-33
Y	US 4 142 656 A (SMITH MICHAEL R ET AL) 6 March 1979 (1979-03-06) column 4, line 33 - line 53; figures 4-7	1-33
Y	WO 89 10192 A (DARUGAR SOHRAB) 2 November 1989 (1989-11-02) page 7, line 16 -page 11, line 18; figures	3,14
Y	US 4 441 532 A (HRUBESH CHARLES F) 10 April 1984 (1984-04-10) the whole document	21

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

6 December 1999

Date of mailing of the international search report

13/12/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Meulemans, J-P

# INTERNATIONAL SEARCH REPORT

Int. Application No  
PCT/US 99/20692

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 607 861 A (KOMATSU AKIHIRO ET AL) 4 March 1997 (1997-03-04) the whole document ---	1-5,8-20
A	US 5 770 151 A (ROACH DAVID J ET AL) 23 June 1998 (1998-06-23) ---	1
A	US 5 763 278 A (BALMER JOHANNES KONRAD ET AL) 9 June 1998 (1998-06-09) the whole document -----	9